

100lm/W

Alta eficiencia
High efficiency
Haute efficacité



6W



Ugradni LED downlight kružni 6W - Prečnik Ø95mm

Ugrađeni LED downlight kružni od 6W, sa vanjskim prečnikom od 118mm i dubinom od 25.5mm. Izrađen od bijelog polikarbonata, nudi efikasno osvjetljenje bez elektromagnetskih šumova, idealno za unutarnje prostore. Prečnik reza: Ø95mm.

Product data

T° svjetlosti	3000°K (koristiti), 4000°K (koristiti), 6000K (koristiti)
Certifikati	CE, ROHS
Razred energetske efikasnosti	A+ (2021)
CRI	80-85
Dimenzije (mm) LxLxh	118x118x25.5
Dimenzije rezanja (mm)	Ø95-100
Prigušivo	Ne
Efikasnost (Lm/w)	100
Oblik	Cirkular
Učestalost korištenja	normalan
Garancija	Prema zakonskoj garanciji: 3 godine
IP	IP20
Kelvin (K)	3000, 4000, 6000
Lumeni (Lm)	600
Materijal	Polikarbonat
Materijalni difuzor	Polikarbonat
Montiranje	Ugradni
Orijentabilan	Ne
Raspon temperature	-20°C ~ +40°C
Nominalni Napon (V)	230
Vrsta LED-a	SMD 2835
Tonalitet	Topla bijela, Bijela hladna, Neutralna bijela



Spoljna upotreba	Ne
Životni vijek (h)	25000

Product variants

Reference	Attributes	
B1241-B-6W-BC	T° svjetlosti : 3000°K (koristiti)	100lm/W Alta eficiencia High efficiency Haute efficacité  6W 
B1241-B-6W-BF	T° svjetlosti : 6000K (koristiti)	100lm/W Alta eficiencia High efficiency Haute efficacité  6W 
B1241-B-6W-BN	T° svjetlosti : 4000°K (koristiti)	100lm/W Alta eficiencia High efficiency Haute efficacité  6W 