



INPUT		LED Driver (LED 控制装置)		DALI-2	
AC-L		Model: LF-GSD040YG		Preparation for input and output	
AC-N		Input: 220-240V~50/60Hz Max.0.3A		7.5mm	
PUSH		U out: 59V~ PF:>0.9C Prated:44.1W(Max)			
DA1		For 2 -Channel LED Driver			
DA2		For Australia and New Zealand, the marking label with "X"			
0.75-1.5					
OUTPUT		Output current and setting table		tc:90°C	
WW-		IS	Vo DC	1050mA	1 2 3 4
WW+				1000mA	OFF OFF OFF OFF
CW+				900mA	OFF OFF ON OFF
CW-				800mA	OFF OFF ON ON
0.5-1.0				700mA	OFF ON ON OFF
ON				600mA	OFF ON ON ON
OFF				550mA	ON OFF ON OFF

Driver LIFUD DALI-2 DT8



DALI PUSH dimmable LIFUD driver 20-42V 40W multicurrent (550-1050mA) CCT2000-7000K

Ref. LF-GSD040YG

Ovladač LIFUD LF-GSD040YG je konstantní proudový LED ovladač 40W s funkcemi stmívání DALI a dimovatelný. Vstupní napětí je 220-240V a výstup 20-42V. Jeho výstupní proud lze nastavit od 550mA do 1050mA pomocí DIP přepínače, po krocích 50mA.

Product data

Certifikáty	CE, ROHS
Výstupní proud mA	550-1050mA
Rozměry (mm) ŠxVxH	80,8x126,2x31,2mm
Stmívatelný	0%-100% (0,1%)
Frekvence (Hz)	50 - 60
IP	IP20
Kelvin (K)	2000-7000K
Materiál	Plast
Maximální výkon (W)	40w
Teplotní rozsah	-20 °C ~ +40 °C
Výstupní napětí (V)	20-42V
Nominální napětí (V)	220-240V

Driver LIFUD DALI-2 DT8



Product variants

Reference

Attributes



LF-GSD040YG