





RGB Amplifier/repeater - Tri-proof 12-24V DC - 4A/channel

Ref. B1625-3

Signal amplifier for LED strips and RGB LED fixtures of 12-24V. Allows extending the length of adjustable LED strip installations using a single controller. The regulation signal will be extended linearly and without delays, ensuring optimal performance at all times. Due to its IP67 protection rating, it is a product suitable for outdoor use.

Certs CE, ROHS Energy efficiency class A+ (2021) Dimensions (mm) LxWxH 95x52x30 Frequency of Use Intensive Guarantee According to legal warranty: 3 years IP IP67 Material Plastic Power (W) 144-288 max. Temperature range -20°F to +60°F	Product data	
Dimensions (mm) LxWxH 95x52x30 Frequency of Use Intensive Guarantee According to legal warranty: 3 years IP IP67 Material Plastic Power (W) 144-288 max.	Certs	CE, ROHS
Frequency of Use Intensive Guarantee According to legal warranty: 3 years IP IP67 Material Plastic Power (W) 144-288 max.	Energy efficiency class	A+ (2021)
Guarantee According to legal warranty: 3 years IP IP67 Material Plastic Power (W) 144-288 max.	Dimensions (mm) LxWxH	95x52x30
IP IP67 Material Plastic Power (W) 144-288 max.	Frequency of Use	Intensive
Material Plastic Power (W) 144-288 max.	Guarantee	According to legal warranty: 3 years
Power (W) 144-288 max.	IP	IP67
	Material	Plastic
Temperature range -20°F to +60°F	Power (W)	144-288 max.
	Temperature range	-20°F to +60°F



Nominal Voltage (V)	12-24V DC	
Outdoor Use	If	
Recommended Use	Garden	
Service life (h)	<n_generated_text>35000</n_generated_text>	

Product variants

Reference Attributes



B1625-3