



Asymmetric LED floodlight 200W - 150lm/W - IP65

Ref. B8221

Asymmetrical LED projector industrial high performance, with a power of 200W and an efficiency of 150lm/W. Its asymmetric lens optimizes light distribution, making it ideal for sports facilities, industrial halls, workshops, or parking lots, among others. Available in cool white (5000K). **7 Year Warranty**



Product data

Opening angle (°)	80 / 150
Certs	CE, ROHS
Energy efficiency class	D
CRI	80-85
Dimensions (mm) LxWxH	438x396x60
Dimmable	No
Driver	Internal
Efficiency (Lm/w)	150
Power factor (cosφ)	0.9
Frequency (Hz)	50 - 60
Frequency of Use	Intensive
Projector Range	Asymmetrical
Guarantee	7 years
IP	IP66
Kelvin (K)	5000
Lumens (Lm)	30000
Material	Aluminum
Material diffuser	Polycarbonate
Orientable	Yes
Power (W)	200
Sensor	No
Nominal Voltage (V)	100-240V

Better Heat Dissipation Multi-board convection cooling design



Type of LED	Chip EPISTAR
Key	Cold white
Outdoor Use	If
Recommended Use	Garden, Industrial Warehouses
Service life (h)	50000

Product variants

Reference	Attributes
B8221	