

100lm/W

Alta eficiencia
High efficiency
Haute efficacité



6W



Recessed circular LED downlight - 6W - Cutout Ø95mm

6W recessed circular LED downlight, with an exterior diameter of 118mm and a depth of 25.5mm. Made of white polycarbonate, it offers efficient lighting and free from electromagnetic noise, ideal for indoor spaces. Cutting diameter: Ø95mm.

Product data

Light temperature	3000°K (use), 4000°K (use), 6000K (use)
Certs	CE, ROHS
Energy efficiency class	A+ (2021)
CRI	80-85
Dimensions (mm) LxWxH	118x118x25.5
Cutting dimensions (mm)	Ø95-100
Dimmable	No
Efficiency (Lm/w)	100
Form	Circular
Frequency of Use	normal
Guarantee	According to legal warranty: 3 years
IP	IP20
Kelvin (K)	3000, 4000, 6000
Lumens (Lm)	600
Material	Polycarbonate
Material diffuser	Polycarbonate
Assembly	Recessed
Orientable	No
Temperature range	-20°F ~ +40°F
Nominal Voltage (V)	230
Type of LED	SMD 2835
Key	Warm white, Cold white, Neutral white



Outdoor Use	No
Service life (h)	25,000

Product variants		
Reference	Attributes	
B1241-B-6W-BC	Light temperature : 3000°K (use)	100lm/W Alta eficiencia High efficiency Haute efficacité   6W
B1241-B-6W-BF	Light temperature : 6000K (use)	100lm/W Alta eficiencia High efficiency Haute efficacité   6W
B1241-B-6W-BN	Light temperature : 4000°K (use)	100lm/W Alta eficiencia High efficiency Haute efficacité   6W