


LED ground recessed spotlight 4,5W 220V-AC IP67

Ref. BA50017-BC

LED recessed floor floodlight with a power of 4.5W. Direct connection to 100-240V/AC. Outdoor LED beacon emitting warm light, at 3000 degrees Kelvin. IP67 protection rating, resistant to rain, preventing the entry of dust and water. Emits a very powerful and concentrated light, thanks to its narrow 30° beam angle. Ideal for use in gardens or in indoor spaces such as staircases. Perfect for bathing walls, columns, vegetation, or any type of structure, whether in gardens, pathways, staircases, patios, buildings... Pedestrian traffic usable 100KG. Includes plastic tube for concrete mounting. 100-240V/AC -4.5W CHIP COB 3000K Ø65x56mm × 56 mm IP67 Cutting diameter 60 mm. Cable length included is 1 meter

Product	data

Light temperature	3000°K (use)
Opening angle (°)	30
Certs	CE, ROHS
Energy efficiency class	A+ (2021)
Dimensions (mm) LxWxH	Ø65x56
Cutting dimensions (mm)	Ø56
Dimmable	Yes
Driver	Not included
Frequency (Hz)	50 - 60
Frequency of Use	normal
Guarantee	According to legal warranty: 3 years
IP	IP67
IP Kelvin (K)	IP67 3000
<u> </u>	
Kelvin (K)	3000
Kelvin (K) Material	3000 Steel
Kelvin (K) Material Material diffuser	3000 Steel Polycarbonate
Kelvin (K) Material Material diffuser Assembly	3000 Steel Polycarbonate Recessed
Kelvin (K) Material Material diffuser Assembly Power (W)	3000 Steel Polycarbonate Recessed 4.5
Kelvin (K) Material Material diffuser Assembly Power (W) Temperature range	3000 Steel Polycarbonate Recessed 4.5 -20°F ~ +40°F
Kelvin (K) Material Material diffuser Assembly Power (W) Temperature range Nominal Voltage (V)	3000 Steel Polycarbonate Recessed 4.5 -20°F ~ +40°F 230





Recommended UseGardenService life (h)25,000

Product variants

Reference

Attributes

7

BA50017-BC Light temperature : 3000°K (use)