



10W
IP55
GX53
LED
CCT
SYSTEM
3000K-4000K-6000K



Mini bollard for LED paths FUMAGALLI "ESTER 500" - GX53 - 10W - CCT



Product data

Housing color	White (use), Black (use), Gray (to use)
Light temperature	CCT (to use)
Cap	GX53
Certs	CE, ROHS
Energy efficiency class	A+ (2021)
Dimensions (mm) LxWxH	175x175x480
Dimmable	No
Frequency (Hz)	50 - 60
Frequency of Use	Intensive
Guarantee	3 years
IP	IP55
Kelvin (K)	4000, 6500, 2700
Material	Resin
Assembly	Surface
Temperature range	-20°F ~ +40°F
Nominal Voltage (V)	100-240
Key	CCT
Outdoor Use	If
Recommended Use	Garden
Service life (h)	25,000



Product variants

Reference	Attributes	
DS1.563.000.AXD1K	Housing color: Black (use), Light temperature : CCT (to use)	 10W IP55 CCT 24V
DS1.563.000.LXD1K	Housing color: Gray (to use), Light temperature : CCT (to use)	 10W IP55 CCT 24V
DS1.563.000.WXD1K	Housing color: White (use), Light temperature : CCT (to use)	 10W IP55 CCT 24V