



Linkable LED tri-proof batten light - 55W 150cm 7150Lm IP65

Ref. B8400-150BN

Sealed LED Panel integrated, 150cm in length and 55W in consumption, ideal for replacing sealed fixtures of conventional fluorescent tubes with an energy savings of up to 50%. It integrates a SANAN SMD2835 LED chip in neutral white 4000K and a frosted cover. Made of PC and resistant to water (IP65 and IK04 against impacts and falls). 58.3x2.8x2.4 inches 55W 230V 7150 Lumens IP65



Product data

Opening angle (°)	120
Certs	CE, ROHS
Energy efficiency class	E
CRI	80-85
Dimensions (mm) LxWxH	1480x72x61
Dimmable	No
Efficiency (Lm/w)	130
Power factor (cosφ)	0.9
Frequency (Hz)	50 - 60
Frequency of Use	Intensive
Guarantee	5 years
IP	IP65
Kelvin (K)	4000
Lumens (Lm)	7150
Material	Polycarbonate
Material diffuser	Polycarbonate
Power (W)	55
Temperature range	-20°F ~ +40°F
Sensor	No
Nominal Voltage (V)	230V AC
Type of LED	SMD 2835
Key	Neutral white



UGR	No
Outdoor Use	If
Service life (h)	25,000

Product variants

Reference	Attributes
B8400-150BN	