







Linkable LED tri-proof light - 40W - 47.2in - IP65

Ref. B8400-120BN

Waterproof LED panel integrated with a length of $120 \, \text{cm}$ and a power of $40 \, \text{W}$, featuring a luminous efficiency of $130 \, \text{LM/W}$, perfect for replacing conventional fluorescent tube panels, with a $50 \, \text{W}$ energy saving. It incorporates a Sanan SMD2835 professional-use LED chip with high brightness. Made from water-resistant polycarbonate (IP65 protection and IK08 rating against impacts and falls). $1180 \, \text{x} \, 22 \, \text{C} \, \text{Imm} \, 40 \, \text{W} \, 230 \, \text{V} \, 5200 \, \text{LM} \, \text{IP65} \, 130 \, \text{LM/W}$



Product data

Opening angle (°)	120
Certs	CE, ROHS
Energy efficiency class	D
CRI	80-85
Dimensions (mm) LxWxH	1180x72x61
Dimmable	No
Efficiency (Lm/w)	130
Power factor (cosφ)	0.9
Frequency (Hz)	50 - 60
Frequency of Use	Intensive
Guarantee	5 years
IK	08
IP	IP65
Kelvin (K)	4000
Lumens (Lm)	5200
Material	Polycarbonate
Material diffuser	Polycarbonate
Temperature range	-20°F ~ +40°F
Sensor	No
Nominal Voltage (V)	230V AC
Type of LED	SMD 2835
Key	Neutral white



1180mm x 72mm



UGR	No
Outdoor Use	If
Recommended Use	Commerce, Parking
Service life (h)	25,000

Product variants

Reference Attributes



B8400-120BN