



Recessed LED marker light in ground 0.5W - 12V DC - IP67 - Ø60mm

Recessed ground marker IP67 Ø60x29.5mm 0.5W (6 SMD3350) 12V-DC with waterproof connector, made of stainless steel and opal polycarbonate, emits light in warm white, cool white, or blue (depending on the chosen model). LED for signaling/decorating. Requires a 12V-DC power supply (not included) 12VDC - 0.5W Ø60x29.5mm ≈Ø53 IP67



Product data

Light temperature	3000°K (use), 4000°K (use), Blue (to use)
Opening angle (°)	120
Certs	CE, ROHS
Dimensions (mm) LxWxH	Ø60x29.5
Guarantee	According to legal warranty: 3 years
IP	IP67
Kelvin (K)	3000, 4000
Lumens (Lm)	7
Material	Stainless steel
Material diffuser	Polycarbonate
Assembly	Recessed in Floor
Type of LED	SMD 2835
Key	Warm white, Neutral white, Blue
Outdoor Use	If
Service life (h)	25,000

Product variants

Reference	Attributes	
BA50010-AZ	Light temperature : Blue (to use)	
BA50010-BC	Light temperature : 3000°K (use)	
BA50010-BN	Light temperature : 4000°K (use)	