





Product data





Waterproof White Square 24W LED Surface Mounted Ceiling Light 2640LM IP54

Square surface LED ceiling light specially designed for damp areas IP54 such as bathrooms, kitchens, laundry rooms, and covered outdoor spaces. High efficiency of 110LM/W and low consumption, only 24W. ✓ 280x280x54mm ✓ 2640LM ✓ 24W - 230V ✓ IP54



| Light temperature | 3000°K (use) |
|-------------------------|--------------|
| Opening angle (°) | 120 |
| Certs | CE, ROHS |
| Energy efficiency class | A+ (2021) |
| CRI | 80-85 |
| Dimensions (mm) LxWxH | 280x280x54 |
| Dimmable | No |
| Driver | Internal |
| Efficiency (Lm/w) | 110 |
| Form | Cuadrado |
| Frequency (Hz) | 50 - 60 |
| Frequency of Use | normal |

| Dimensions (mm) LxWxH | 280x280x54 |
|-----------------------|--------------------------------------|
| Dimmable | No |
| Driver | Internal |
| Efficiency (Lm/w) | 110 |
| Form | Cuadrado |
| Frequency (Hz) | 50 - 60 |
| Frequency of Use | normal |
| Guarantee | According to legal warranty: 3 years |
| IP | IP54 |
| Kelvin (K) | 3000, 4000 |
| Material | Plastic |
| Material diffuser | Polycarbonate |
| Assembly | Surface |
| Orientable | No |
| Power (W) | 24 |
| Temperature range | -20°F ~ +40°F |
| Sensor | No |





| Nominal Voltage (V) | 230 |
|---------------------|---------------------------|
| Type of LED | SMD 2835 |
| Key | Warm white, Neutral white |
| Outdoor Use | If |
| Recommended Use | Garden |
| Service life (h) | 25,000 |

Product variants

Reference Attributes



B1720-C-BC Light temperature : 3000°K (use)