



LED recessed panel - 120X30cm - 0-10V dimmable - 44W - UGR19

The recessed LED panel 120 x 30 cm features an ultra-slim design and cutting-edge technology that allows it to provide powerful and uniform lighting. Highly efficient, it has a power of 44W and a luminous flux of 2900 lumens. It incorporates a 0-10V dimming driver, which provides the ability to adjust the light intensity. Thanks to its low glare level, UGR19, this panel provides great visual comfort. Available in three shades: warm white (3000K), neutral white (4000K), and cool white (6000K).



Product data

Light temperature	Cold White (DO NOT USE) , Warm White , Neutral White
Certs	CE, ROHS
CRI	80-85
Dimensions (mm) LxWxH	1200 x 300 x 6
Cutting dimensions (mm)	1200x300
LED Panel Dimensions	120x30
Dimmable	Yes
Frequency (Hz)	50 - 60
Frequency of Use	Intensive
Guarantee	According to legal warranty: 3 years
IP	IP20
Kelvin (K)	3000, 4000, 6000
Lumens (Lm)	2900
Material diffuser	Polycarbonate
Assembly	Recessed
Orientable	No
Power (W)	44
Sensor	No
Nominal Voltage (V)	220 - 240 V AC
Type of LED	SMD 2835
Key	Warm white, Cold white, Neutral white
UGR	UGR19



Outdoor Use	No
Service life (h)	25,000

Product variants

Reference

Attributes

K5236-O-10-BC

Light temperature : Warm White



K5236-O-10-BF

Light temperature : Cold White (DO NOT USE)



K5236-O-10-BN

Light temperature : Neutral White

