



Recessed LED Panel - 120X60cm - PUSH Dimmable - 72W - UGR19

The 120 x 60 cm recessed LED panel features an ultra-slim design and cutting-edge technology that enables it to provide powerful and even lighting. Highly efficient, it has a power of 72W and a luminous flux of 5900 lumens. It incorporates two PUSH regulation drivers, which provides the ability to adjust the light intensity. Thanks to its low glare index, UGR19, this panel provides great visual comfort. Available in three shades: warm white (3000K), neutral white (4000K), and cool white (6000K).



Product data

Light temperature	Cold White (DO NOT USE) , Warm White , Neutral White
Opening angle (°)	120
Certs	CE, ROHS
CRI	80-85
Dimensions (mm) LxWxH	1200 x 600 x 6
Cutting dimensions (mm)	1200x600
LED Panel Dimensions	120x60
Dimmable	Yes
Efficiency (Lm/w)	85
Frequency (Hz)	50 - 60
Frequency of Use	Intensive
Guarantee	According to legal warranty: 3 years
IP	IP20
Kelvin (K)	3000, 4000, 6000
Lumens (Lm)	5900
Material diffuser	Polycarbonate
Assembly	Recessed
Orientable	No
Power (W)	72
Temperature range	-18°F ~ +55°F
Sensor	No
Nominal Voltage (V)	220 - 240 V AC



Type of LED	SMD 2835
Key	Warm white, Cold white, Neutral white
UGR	UGR19
Outdoor Use	No
Service life (h)	25,000

Product variants

Reference

Attributes

K5234-PUSH-BC

Light temperature : Warm White



K5234-PUSH-BF

Light temperature : Cold White (DO NOT USE)



K5234-PUSH-BN

Light temperature : Neutral White

