







## High power CCT LED linear luminaire - 40W - 120cm


## Ref. B8596-CCT-120

120 cm LED linear luminaire with 40W power, especially useful for replacing traditional fluorescent tubes, achieving a great energy savings. Provides high-quality lighting, without flicker, with a luminous efficiency of 120lm/W and a CRI>80. It incorporates a CCT selector, which allows you to change the color temperature between three different shades: warm white (3000K), neutral white (4000K), and cool white (6000K). \*\*Includes: screws and a set of metal staples for fastening\*\*



Prod	ı	ict	А	ata	
Proa	II.	ICI.	а	ara	

Light temperature	CCT (to use)
Opening angle (°)	120
Certs	CE, ROHS
Energy efficiency class	E
CRI	80-85
Dimensions (mm) LxWxH	1200 x 62 x 64
Dimmable	No
Efficiency (Lm/w)	100
Power factor (cosφ)	0.9
Frequency (Hz)	50 - 60
Frequency of Use	normal
Guarantee	According to legal warranty: 3 years
IP	IP20
Kelvin (K)	3000, 4000, 6000
Lumens (Lm)	4800
Lumens (Lm)  Material	4800 Metal
Material	Metal
Material Material diffuser	Metal Polycarbonate
Material Material diffuser Power (W)	Metal Polycarbonate 40
Material Material diffuser Power (W) Temperature range	Metal Polycarbonate 40 -20°F ~ +40°F
Material Material diffuser Power (W) Temperature range Sensor	Metal Polycarbonate 40 -20°F ~ +40°F No





Key	Warm white, Cold white, Neutral white
UGR	No
Outdoor Use	No
Service life (h)	25,000

## **Product variants**

Reference Attributes

B8596-CCT-120 Light temperature : CCT (to use)