


KIT - Recessed square downlight ring 93x93mm (white/black) + 5.4W GU10 Bulb + Socket

Complete lighting kit composed of: Adjustable square downlight with low UGR - White color with champagne interior. GU10 5.4W LED Bulb - Available in 3 shades: warm white, neutral, and cool Pre-wired GU10 lamp holders made of ceramic.



Product data

Case color	White and champagne (use), Black and champagne (use), Black and White (use), Gray and White (use), Gray and Black (use)
Light temperature	2700°K (use), 4000°K (use), 6000K (use)
Cap	GU10
Certs	CE, ROHS
Dimensions (mm) LxWxH	93 x 93 x 29
Cutting dimensions (mm)	Ø75, Ø 75
Efficiency (Lm/w)	130
Guarantee	According to legal warranty: 3 years
IP	IP20
Kelvin (K)	4000, 6000, 2700
Kit	Yes
Material	Polycarbonate, Lightbulb: Glass
Material diffuser	Polycarbonate
Assembly	Recessed
Orientable	Yes
Key	Warm white, Cold white, Neutral white
Outdoor Use	No
Recommended Use	Dining room, Bedrooms, Hotels, Kitchens, Commerce
Power (W)	5.4



Product variants

Reference	Attributes
K921-CB-BC	Case color : White and champagne (use), Light temperature : 2700°K (use)



Reference	Attributes	
K921-CB-BF	Case color : White and champagne (use), Light temperature : 6000K (use)	
K921-CB-BN	Case color : White and champagne (use), Light temperature : 4000°K (use)	
K921-CN-BC	Case color : Black and champagne (use), Light temperature : 2700°K (use)	
K921-CN-BF	Case color : Black and champagne (use), Light temperature : 6000K (use)	
K921-CN-BN	Case color : Black and champagne (use), Light temperature : 4000°K (use)	
K921-GB-BC	Case color : Gray and White (use), Light temperature : 2700°K (use)	
K921-GB-BF	Case color : Gray and White (use), Light temperature : 6000K (use)	
K921-GB-BN	Case color : Gray and White (use), Light temperature : 4000°K (use)	

Reference	Attributes	
K921-GN-BC	Case color : Gray and Black (use), Light temperature : 2700°K (use)	
K921-GN-BF	Case color : Gray and Black (use), Light temperature : 6000K (use)	
K921-GN-BN	Case color : Gray and Black (use), Light temperature : 4000°K (use)	
K921-NB-BC	Case color : Black and White (use), Light temperature : 2700°K (use)	
K921-NB-BF	Case color : Black and White (use), Light temperature : 6000K (use)	
K921-NB-BN	Case color : Black and White (use), Light temperature : 4000°K (use)	