




Pack x 2 - Outdoor LED floodlights - 150W - 95lm/W - IP65

PACK X 2 LED projectors 150W with a compact design, metal case, and glass diffuser. They are adjustable and have an efficiency of 95lm/W. Suitable for outdoor use thanks to its IP65 protection rating. Available in cool white (6000K).



Product data

Light temperature	3000°K (use), 4000°K (use), 6000K (use)
High	38mm
Width	245mm
Opening angle (°)	120
Certs	CE, ROHS
Energy efficiency class	F
Driver	Internal
Frequency (Hz)	50 - 60
Frequency of Use	normal
Projector Range	Slim Series, Packs
IP	IP65
Kelvin (K)	6000
Long	340mm
Lumens (Lm)	10202lm (CW)
Material	Aluminum
Material diffuser	Crystal
Assembly	Surface
Orientable	Yes
Power (W)	150
Sensor	No
Nominal Voltage (V)	220 - 240 V AC
Type of LED	SMD 2835



Key	Cold white
UGR	No
Outdoor Use	If
Recommended Use	Garden
Service life (h)	25,000

Product variants		
Reference	Attributes	
K1885-2-BC	Light temperature : 3000°K (use)	 LOT OF 2 IP65 150W
K1885-2-BF	Light temperature : 6000K (use)	 LOT OF 2 IP65 150W
K1885-2-BN	Light temperature : 4000°K (use)	 LOT OF 2 IP65 150W