

Downlight LED Mini 3W - OSRAM Chip - Low UGR - CRI 90 - Ø 40mm

Product data

Case color	White (use), Black (use)
Light temperature	3000°K (use), 4000°K (use), 6500K (use)
Opening angle (°)	30
Certs	CE, ROHS
CRI	90-95
Dimensions (mm) LxWxH	Ø40x32.1
Cutting dimensions (mm)	Ø35
Driver	Lifud
Form	Circular
Frequency (Hz)	50 - 60
Guarantee	5 years
IP	IP20
Kelvin (K)	2700
Material	Aluminum
Assembly	Recessed
Orientable	No
Sensor	No
Nominal Voltage (V)	220 - 240 V AC
Type of LED	OSRAM Chip
Key	Warm white

UGR	UGR18
Outdoor Use	No

Product variants

Reference	Attributes	
B1251-B-270	Case color : White (use), Light temperature : 3000°K (use)	-
B1251-B-4000	Case color : White (use), Light temperature : 4000°K (use)	-
B1251-B-6000	Case color : White (use), Light temperature : 6500K (use)	-
B1251-N-270	Case color : Black (use), Light temperature : 3000°K (use)	-
B1251-N-4000	Case color : Black (use), Light temperature : 4000°K (use)	-
B1251-N-6000	Case color : Black (use), Light temperature : 6500K (use)	-