



INPUT		LED Driver (LED 控制装置)		DALI	
AC-L		Model: LF-GSD040YG		Preparation for input and output	
AC-N		Input: 220-240V~50/60Hz Max.0.3A		7.5mm	
PUSH		U out: 59V $\pm$ PF:>0.9C Prated:44.1W(Max)			
DA1		For 2 -Channel LED Driver			
DA2		For Australia and New Zealand, the marking label with "X"			
0.75-1.5					
OUTPUT		Output current and setting table		tc:90°C	
WW-		IS	Vo DC	1050mA	OFF OFF OFF OFF
WW+				1000mA	OFF OFF OFF ON
CW+				900mA	OFF OFF ON OFF
CW-				800mA	OFF OFF ON ON
0.5-1.0				700mA	OFF ON OFF OFF
ON				600mA	OFF ON ON OFF
OFF				550mA	ON OFF ON OFF

Driver LIFUD DALI-2 DT8



DALI PUSH dimmable LIFUD driver 20-42V 40W multicurrent (550-1050mA) CCT2000-7000K

Ref. LF-GSD040YG

LIFUD Driver LF-GSD040YG on pidev vool LED juht, mille võimsus on 40W, DALI dimmimis- ja dimmimisfunktsioonidega. Sisendvoltage on 220-240V ja väljund on 20-42V. Selle väljundvoolu saab reguleerida 550mA kuni 1050mA lahti keeramise DIP lüliti kaudu, sammudega 50mA.

Product data

Certifikaadid	CE, ROHS
Väljundvool mA	550-1050mA
Dimensioonid (mm) Pxlxx	80.8x126.2x31.2mm
Dimmable translates to Estonian as hämarasummutus.	0%-100% (0.1%)
Frekvents (Hz)	50 - 60
IP	IP20
Kelvin (K)	2000-7000K
Materjal	Plastik
Maximaalne võimsus (W)	40w
Temperatuuri vahemik	-20°C ~ +40°C
Väljundpinge (V)	20-42V
Nominiaalpinge (V)	220-240V

Driver LIFUD DALI-2 DT8



Product variants

Reference

Attributes



LF-GSD040YG