



Support Common LED Driver ICs on the Market



WS2811	SM16703	TM1814	WS2815
WS2812B	TM1804	TM1913	WS2818
WS2813	UCS1903	P9813	P943S
WS2801	LPD6803	INK1003	P9411
SK6812	LPD6806	DMA512	P9413
SK6812-RGBW	APA102	APA105	TX1812
TX1813	GS8206	GS8208	SK9622
P9414	P9412		

It can support WS2812B and WS2813. But there is no options on setting page.
Please choose WS2811 if connect it to WS2812B and WS2813.
It can't support 5050 ordinary RGB LED strips with no ICs.

WiFi RGB/RGBW pixel IC LED controller - 5-24V DC - 2048 pixels

Ref. SP108E

LED IC kontrollor on loodud RGB/RGBW LED riba kaugkontrollimiseks nutitelefoni. See toimib sisendpingega vahemikus 5 kuni 24V DC ja suudab juhtida kuni 2048 pikslit. Sa saad valida mis tahes efekti või stseeni 180 eelnevalt määratletud mitmevärvilise mustri ja 8 ühevärvilise mustri hulgast. Samuti võimaldab see luua kohandatud mustreid piltidest. Heledust ja kiirus on reguleeritavad. See on hõlpsasti kontrollitav WiFi kaudu rakenduse abil, mis tuleb mobiilseadmesse alla laadida.



Product data

Certifikaadid	CE, ROHS
Energiatõhususe klass	A+ (2021)
Ühenduvus	WiFi
Garantii	3 aastat
IP	IP20
Materjal	Plastik
Avastamise vahemik (m)	30
Temperatuuri vahemik	-20°C ~ +40°C
Nominiaalpinge (V)	5-24V
Toon	RGB
Väline kasutamine	Ei



Product variants

Reference

Attributes

SP108E

