



Pack of 4 slim LED panels 120X30 cm - Driver Philips - 44W - UGR19

PAK x 4 Ugradne LED panele 120X30 cm - Philips driver. Elegantne i ultra tanke ploče s naprednom tehnologijom za snažno i ravnomjerno osvjetljenje u tri nijanse bijele (3000K, 4000K, 6000K). Imaju snagu od 44W i svjetlosni tok od 2900 lumena. Idealni za urede, konferencijske dvorane, škole ili bolnice. Visoki indeks kromatske reprodukcije (CRI>80) za preciznu reprodukciju boja i nizak indeks blještjenja (UGR≤19). Mogu se montirati na lažne stropove ili u gips-kartonske pregrade s okvirom za ugradnju (nije uključeno).



Product data

T° svjetlosti: Bijeli Hlad (NE KORISTI), Topla Bijela (NE KORISTITI), Neutralna bijela (NE KORISTITI)	
Certifikati	CE, ROHS
CRI	80-85
Dimenzije (mm) LxIxh	1200x300x6mm
Dimenzije rezanja (mm)	1200x300mm
Dimenzije LED panela	120x30
Smanjivo	Opcionalno, zamjenjujući upravljač
Vozač	Vanjski
Frekvencija (Hz)	50 - 60
Frekvencija korištenja	Intenzivno
Jamstvo	3 godine
IP	IP65
Kelvin (K)	3000, 4000, 6000
Materijalni difuzor	Polikarbonat
Montiranje	Ugradbeni
Snaga (W)	44
Sensor translates to Croatian as Sensor.	Ne
Nomin tension (V)	230
Vrsta LED-a	SMD 2835
Tonalitet	Topla bijela, Bjela hladna, Bela neutra
Vanjska upotreba	Ne
Radni vijek (h)	25000

⇔ Driver Philips 123x43mm



Product variants

Reference	Attributes	
K5236-4-BC	T° svjetlosti : Topla Bijela (NE KORISTITI)	
K5236-4-BF	T° svjetlosti : Bijeli Hlad (NE KORISTI)	
K5236-4-BN	T° svjetlosti : Neutralna bijela (NE KORISTITI)	