



Support Common LED Driver ICs on the Market



WS2811	SM16703	TM1814	WS2815
WS2812B	TM1804	TM1913	WS2818
WS2813	UCS1903	P9813	P943S
WS2801	LPD6803	INK1003	P9411
SK6812	LPD6806	DMA512	P9413
SK6812-RGBW	APA102	APA105	TX1812
TX1813	GS8206	GS8208	SK9622
P9414	P9412		

It can support WS2812B and WS2813. But there is no options on setting page.
Please choose WS2811 if connect it to WS2812B and WS2813.
It can't support 5050 ordinary RGB LED strips with no ICs.

WIFI RGB/RGBW pixel IC LED controller - 5-24V DC - 2048 pixels

Ref. SP108E

LED IC kontroler je dizajniran za daljinsko upravljanje RGB/RGBW LED IC trakama putem mobilnog telefona, radi s ulaznom naponom od 5 do 24V DC i može kontrolirati do 2048 piksela. Possible je odabrati bilo koji efekt ili scenu iz 180 unaprijed postavljenih multikolor uzoraka i 8 monokromatskih uzoraka. Također omogućuje stvaranje vlastitih uzoraka na temelju slika. Svjetlina i brzina mogu se prilagoditi. Lako se kontrolira putem WiFi-a putem aplikacije koju treba preuzeti na mobilni uređaj.



Product data

Certifikati	CE, ROHS
Razred energetske učinkovitosti	A+ (2021)
Povezanost	Wifi
Jamstvo	3 godine
IP	IP20
Materijal	Plastika
Raspon detekcije (m)	30
Raspon temperature	-20°C ~ +40°C
Nomin tension (V)	5-24V
Tonalitet	RGB
Vanjska upotreba	Ne



Product variants

Reference

Attributes

SP108E

