



RGB+CCT 50W 4200lm RGB+CCT 50W LED floodlight - RF and WiFi control - IP65 FUTT02

Ref. FUTT02



Product data

Kut otvora (°)	160
Certifikati	CE, ROHS
Razred energetske učinkovitosti	A+ (2021)
Povezanost	WIFI
CRI	80-85
Dimenzije (mm) LxLxh	220x310x50
Smanjivo	Da
Vozač	Unutarnji
Učinkovitost (Lm/w)	84
Faktor snage (cosφ)	0,9
Frekvencija (Hz)	50 - 60
Frekvencija korištenja	Intenzivno
Gama projektora	RGB
Jamstvo	Prema zakonskoj garanciji: 3 godine
IP	IP65
Kelvin (K)	6500, 2700

Lumeni (Lm)	4200
Materijal	Metal
Materijalni difuzor	Kristal
Montiranje	Površina
Orijentabilan	Da
Peso (g)	1900
Snaga (W)	50
Raspon temperature	-20°C ~ +40°C
Sensor translates to Croatian as Sensor.	Ne
Nomin tension (V)	86-265
Vrsta LED-a	SMD 3030
Tonalitet	Topla bijela, Bjela hladna, RGB
UGR	Ne
Vanjska upotreba	Da
Preporučena upotreba	Vrt
Radni vijek (h)	50000

Product variants

Reference

Attributes

FUTT02

