

LED kružni ugradbeni downlight 25W - Profesionalna upotreba - Ø190 mm

Product data

T° svjetlosti	3000°K (koristiti), 4000°K (koristiti), 6500K (koristiti)
Kut otvora (°)	100
Certifikati	CE, ROHS
Razred energetske učinkovitosti	F
CRI	80-85
Dimenzije (mm) LxIxh	Ø230x35
Dimenzije rezanja (mm)	Ø187
Smanjivo	Ne
Učinkovitost (Lm/w)	114
Faktor snage (cosφ)	0,98
Oblik	Cirkular, Ultrafino
Frekvencija (Hz)	50 - 60
Frekvencija korištenja	Intenzivno
Jamstvo	3 godine
IP	IP20
Kelvin (K)	3000, 4000, 6000
Materijal	Aluminij
Montiranje	Ugradbeni
Orijentabilan	Ne
Snaga (W)	25

Raspon temperature	-20°C ~ +40°C
Sensor translates to Croatian as Sensor.	Ne
Nomin tension (V)	230V AC
Vrsta LED-a	SMD 2835
Tonalitet	Topla bijela, Bjela hladna, Bela neutra
Vanjska upotreba	Ne
Radni vijek (h)	25000

Product variants

Reference	Attributes	
B1264BC	T° svjetlosti : 3000°K (koristiti)	
B1264BF	T° svjetlosti : 6500K (koristiti)	
B1264BN	T° svjetlosti : 4000°K (koristiti)	