

Ugradna LED kružna downlight 6W - Promjer Ø 110 mm - 5 godina garancije

Product data

T° svjetlosti	3000°K (koristiti), 4000°K (koristiti), 6500K (koristiti)
Kut otvora (°)	120
Certifikati	CE, ROHS
Razred energetske učinkovitosti	A+ (2021)
CRI	80-85
Dimenzije (mm) LxIxh	Ø116x15
Dimenzije rezanja (mm)	Ø110
Smanjivo	Ne
Učinkovitost (Lm/w)	75
Faktor snage (cosφ)	0,5
Oblik	Cirkular, Ultrafino
Frekvencija korištenja	normalan
Jamstvo	5 godina
IP	IP20
Kelvin (K)	3000, 4000, 6000
Lumeni (Lm)	450
Materijal	Aluminij
Materijalni difuzor	Polikarbonat
Montiranje	Ugradbeni
Orijentabilan	Ne

Raspon temperature	-20°C ~ +40°C
Sensor translates to Croatian as Sensor.	Ne
Nomin tension (V)	230V AC
Vrsta LED-a	SMD 2835
Tonalitet	Topla bijela, Bjela hladna, Bela neutra
Vanjska upotreba	Ne
Radni vijek (h)	25000

Product variants

Reference	Attributes	
B1070-BC	T° svjetlosti : 3000°K (koristiti)	
B1070-BF	T° svjetlosti : 6500K (koristiti)	
B1070-BN	T° svjetlosti : 4000°K (koristiti)	