



INPUT		LED Driver (LED 控制装置)		DALI	
AC-L		Model: LF-GSD040YG		Preparation for input and output	
AC-N		Input: 220-240V~50/60Hz Max.0.3A		7.5mm	
PUSH		U out: 59V~ PF:>0.9C Prated:44.1W(Max)		For 2 -Channel LED Driver	
DA1		For Australia and New Zealand, the marking label with "X"		Output current and setting table	
DA2		0.75-1.5		tc:90°C	
				www.lifud.com	
				Made in China	
				(中国制造)	
				CE SELV	
OUTPUT		IS Vo DC		1 2 3 4	
WW-		1050mA		OFF OFF OFF OFF	
WW+		1000mA		OFF OFF OFF ON	
CW+		900mA		OFF OFF ON OFF	
CW-		800mA		OFF OFF ON ON	
0.5-1.0		700mA		OFF ON OFF OFF	
		600mA		OFF ON OFF ON	
		550mA		ON OFF OFF OFF	
				ON OFF ON OFF	

Driver LIFUD DALI-2 DT8



DALI PUSH dimmable LIFUD driver 20-42V 40W multicurrent (550-1050mA) CCT2000-7000K

Ref. LF-GSD040YG

LIFUD Driver LF-GSD040YG egy állandó áramú LED meghajtó 40W teljesítménnyel, DALI fényerőszabályozással és dimmelhető funkciókkal. A bemeneti feszültség 220-240V, míg a kimenet 20-42V. A kimeneti áram 550mA-tól 1050mA-ig állítható a DIP kapcsolóval, 50mA lépésekben.

Product data

Tanúsítványok	CE, ROHS
Kimeneti áram mA	550-1050mA
Dimenziók (mm) HxLxsz	80,8x126,2x31,2mm
Dimmerelhető	0%-100% (0,1%)
Frekvencia (Hz)	50 - 60
IP	IP20
Kelvin (K)	2000-7000K
Anyag	Műanyag
Maximális teljesítmény (W)	40w
Hőmérsékleti tartomány	-20 °C ~ +40 °C
Kimeneti feszültség (V)	20-42V
Névleges Feszültség (V)	220-240V

Driver LIFUD DALI-2 DT8



Product variants

Reference

Attributes



LF-GSD040YG