



INPUT		LED Driver (LED 控制装置)		DALI-2	
AC-L		Model: LF-GSD040YG		Preparation for input and output	
AC-N		Input: 220-240V~50/60Hz Max.0.3A		7.5mm	
PUSH		U out: 59V~ PF:>0.9C Prated:44.1W(Max)			
DA1		For 2 -Channel LED Driver			
DA2		For Australia and New Zealand, the marking label with "X"			
0.75-1.5					
OUTPUT		Output current and setting table		tc:90°C	
WW-		IS	Vo DC	1050mA	OFF OFF OFF OFF
WW+				1000mA	OFF OFF OFF ON
CW+				900mA	OFF OFF ON OFF
CW-				800mA	OFF OFF ON ON
0.5-1.0				700mA	OFF ON OFF OFF
ON				600mA	OFF ON ON OFF
OFF				550mA	ON OFF OFF ON

Driver LIFUD DALI-2 DT8



DALI PUSH dimmable LIFUD driver 20-42V 40W multicurrent (550-1050mA) CCT2000-7000K

Ref. LF-GSD040YG

LIFUD Treiber LF-GSD040YG ass e konstanten Stroum LED-Treiber vu 40W mat DALI Dimmer- an dimmbar Funktiounen. D' Inputspannung ass 220-240V an d'Output ass 20-42V. Seng Outputstrom kann vun 550mA bis 1050mA iwwer de DIP Schalter justéiert ginn, zu Schrëtt vu 50mA.

Product data

Certificaten	CE, ROHS
Erausgangsstrom mA	550-1050mA
Dimensiounen (mm) LxIxh	80,8x126,2x31,2mm
dimmbars	0%-100% (0,1%)
Frequenz (Hz)	50 - 60
IP	IP20
Kelvin (K)	2000-7000K
Material	Plastik
Maximal Leeschtung (W)	40w
Temperaturbereich	-20°C ~ +40°C
Ausgangsspannung (V)	20-42V
Nummspannung (V)	220-240V

Driver LIFUD DALI-2 DT8



Product variants

Reference

Attributes



LF-GSD040YG