

Driver DALI-2 DT8 LIFUD



LIFUD dimmable DALI PUSH driver 9-42V 12W multicurrent (100-350mA) CCT2000-7000K

Ref. LF-GSD012YK

LIFUD Driver LF-GSD012YK aus der DALI-2 DT8 Serie ass e konstanten Aarbechtsstrooss LED Treiber vun 12W mat dimmbar CCT DALI Funktionalitéit. D'Inputspannung Gamme ass 220-240V an d'Ausgabespannung ass 9-42V. Seng Ausgabestrom kann vun 100mA bis 350mA iwwer den DIP Schalter justéiert ginn, an Inkrementer vun 50mA. Maximal Last op 83%(230VAC).

Product data

Certificaten	CE, ROHS
Erausgangsstrom mA	100-350mA
Dimensiounen (mm) LxIxH	39.9x121x25
dimmbar	0%-100% (0,1%)
Frequenz (Hz)	50 - 60
IP	IP20
Kelvin (K)	2700K-6500K CCT
Material	Plastik
Maximal Leeschtung (W)	12W
Temperaturbereich	-20°C ~ +40°C
Ausgangsspannung (V)	9-42V
Nummspannung (V)	220-240V

Driver DALI-2 DT8 LIFUD



Product variants

Reference

Attributes



LF-GSD012YK