



**Support Common LED Driver ICs on the Market**



|             |         |         |        |
|-------------|---------|---------|--------|
| WS2811      | SM16703 | TM1814  | WS2815 |
| WS2812B     | TM1804  | TM1913  | WS2818 |
| WS2813      | UCS1903 | P9813   | P943S  |
| WS2801      | LPD6803 | INK1003 | P9411  |
| SK6812      | LPD6806 | DMA512  | P9413  |
| SK6812-RGBW | APA102  | APA105  | TX1812 |
| TX1813      | GS8206  | GS8208  | SK9622 |
| P9414       | P9412   |         |        |

It can support WS2812B and WS2813. But there is no options on setting page.  
Please choose WS2811 if connect it to WS2812B and WS2813.  
It can't support 5050 ordinary RGB LED strips with no ICs.

## WIFI RGB/RGBW pixel IC LED controller - 5-24V DC - 2048 pixels

### Ref. SP108E

De LED IC Controller ass entworfen fir RGB/RGBW LED Sträifen aus der Distanz mat engem Handy ze steieren. Et huet eng Input-Spannung von 5 bis 24V DC an kann bis zu 2048 Pixels contrôlëieren. Et ass méiglech, all Effekt oder Szenee vun 180 virdru festgeluegten multifaarwege Musteren a 8 monokrome Musteren ze wielen. Et erlaabt och d'Erstellung vun eegene Musteren aus Biller. D'Luuchtegen an d'Geschwindigkeit si justéierbar. Et ass einfach iwwer WiFi duerch eng App ze kontrolléieren, déi op dem mobilen Apparat erofgelueden muss ginn.



### Product data

|                             |               |
|-----------------------------|---------------|
| Certificaten                | CE, ROHS      |
| Klasse énergéiert Effizient | A+ (2021)     |
| Verbindung                  | Wifi          |
| Garantie                    | 3 Joer        |
| IP                          | IP20          |
| Material                    | Plastik       |
| Detektéierberäich (m)       | 30            |
| Temperaturbereich           | -20°C ~ +40°C |
| Nummspannung (V)            | 5-24V         |
| Tonalitéit                  | RGB           |
| Uwendung am Freien          | Nei           |



Product variants

Reference

Attributes

SP108E

