

Downlight LED ronn emporbaut 25W - Professionell

Benotzung - Ø190 mm

Product data

T° vum Liicht	3000°K (benotzen), 4000°K (benotzen), 6500K (benotzen)
Winkelope (°)	100
Certificaten	CE, ROHS
Klasse énérgéiert Effizient	F
CRI	80-85 in Luxembourgish is 80-85.
Dimensiounen (mm) LxIxh	Ø230x35
Schneiddimensiounen (mm)	Ø187
dimmbars	Nei
Effizienz (Lm/w)	114
Leedungsfaktor (cosφ)	0,98
Form	Ronderëm, Ultrafin
Frequenz (Hz)	50 - 60
Benotzungsfrequenz	Intensiv
Garantie	3 Joer
IP	IP20
Kelvin (K)	3000, 4000, 6000
Material	Aluminium
Montage	Versenkbar
Orientéierbar	Nei
Leistung (W)	25

Temperaturbereich	-20°C ~ +40°C
Sensor	Neen
Nummspannung (V)	230V AC
Typ vum LED	SMD 2835
Tonalitéit	Warme Wäiss, Fréisch Wäiss, Neutral Weiß
Uwendung am Freien	Nei
Letztenzäit (h)	25.000

Product variants

Reference	Attributes	
B1264BC	T° vum Liicht : 3000°K (benotzen)	
B1264BF	T° vum Liicht : 6500K (benotzen)	
B1264BN	T° vum Liicht : 4000°K (benotzen)	