



INPUT		LED Driver (LED 控制装置)		DALI-2	
AC-L		Model: LF-GSD040YG		Preparation for input and output	
AC-N		Input: 220-240V~50/60Hz Max.0.3A		7.5mm	
PUSH		U out: 59V $\pm$ PF:>0.9C Prated:44.1W(Max)			
DA1		For 2 -Channel LED Driver			
DA2		For Australia and New Zealand, the marking label with "X"			
0.75-1.5					
OUTPUT		Output current and setting table		tc:90°C	
WW-		IS	Vo DC	1050mA	OFF OFF OFF OFF
WW+				1000mA	OFF OFF OFF ON
CW+				900mA	OFF OFF ON OFF
CW-				800mA	OFF OFF ON ON
0.5-1.0				700mA	OFF ON OFF OFF
ON				600mA	OFF ON ON OFF
OFF				550mA	ON OFF ON OFF

Driver LIFUD DALI-2 DT8



DALI PUSH dimmable LIFUD driver 20-42V 40W multicurrent (550-1050mA) CCT2000-7000K

Ref. LF-GSD040YG

Driver LIFUD LF-GSD040YG este un driver LED cu curent constant de 40W cu dimming DALI și funcții dimmabile. Tensiunea de alimentare este de 220-240V iar ieșirea este de 20-42V. Curentul de ieșire poate fi ajustat de la 550mA la 1050mA prin intermediul switch-ului DIP, în pași de 50mA.

Product data

Certificatul	CE, ROHS
Curent de ieșire mA	550-1050mA
Dimensiuni (mm) LxIxh	80.8x126.2x31.2mm
Reglabil	0%-100% (0.1%)
Frecvență (Hz)	50 - 60
IP	IP20
Kelvin (K)	2000-7000K
Material	Plastic
Puterea maximă (W)	40w
Interval de temperatură	-20°C ~ +40°C
Tensiune de ieșire (V)	20-42V
Tensiune Nominală (V)	220-240V

Driver LIFUD DALI-2 DT8



Product variants

Reference

Attributes



LF-GSD040YG