



INPUT		LED Driver (LED 控制装置)		DALI	
AC-L		Model: LF-GSD040YG		Preparation for input and output	
AC-N		Input: 220-240V~50/60Hz Max.0.3A		7.5mm	
PUSH		U out: 59V $\pm$ PF:>0.9C Prated:44.1W(Max)			
DA1		For 2 -Channel LED Driver			
DA2		For Australia and New Zealand, the marking label with "X"			
0.75-1.5					
OUTPUT		Output current and setting table		tc:90°C	
WW-		IS	Vo DC	1000mA	OFF OFF OFF OFF
WW+				1000mA	OFF OFF OFF ON
CW+				900mA	OFF OFF ON OFF
CW-				900mA	OFF OFF ON ON
0.5-1.0				850mA	OFF ON OFF OFF
ON				850mA	OFF ON OFF ON
OFF				800mA	OFF ON OFF ON
				750mA	OFF ON ON OFF
				700mA	OFF ON ON ON
				650mA	ON OFF OFF OFF
				600mA	ON OFF OFF ON
				550mA	ON OFF ON OFF

Driver LIFUD DALI-2 DT8



DALI PUSH dimmable LIFUD driver 20-42V 40W multicurrent (550-1050mA) CCT2000-7000K

Ref. LF-GSD040YG

LIFUD Driver LF-GSD040YG je LED driver s konštantným prúdom s výkonom 40W, ktorý má DALI stmievanie a funkcie stmievania. Vstupné napätie je 220-240V a výstupné napätie je 20-42V. Jeho výstupný prúd je možné nastaviť od 550mA do 1050mA pomocou DIP prepínača, po krokoch 50mA.

Product data

Certifikáty	CE, ROHS
Výstupný prúd mA	550-1050mA
Rozmery (mm) D×Š×V	80,8×126,2×31,2mm
Nastaviteľné	0%-100% (0,1%)
Frekvencia (Hz)	50 - 60
IP	IP20
Kelvin (K)	2000-7000K
Materiál	Plast
Maximálny výkon (W)	40w
Teplotný rozsah	-20 °C ~ +40 °C
Výstupné napätie (V)	20-42V
Nominálne napätie (V)	220-240V

Driver LIFUD DALI-2 DT8



Product variants

Reference

Attributes



LF-GSD040YG