


## Aplikacija za strop "SARA" 40W Driver PHILIPS

Cilindrična LED stropna svetilka. Phillips gonilnik. COB čip. Idealna za namestitev v trgovinah, izložbah, hotelih in kateremkoli notranjem prostoru. Narejena iz visoko kakovostnega aluminija, prekrita z belo barvo. Ta LED osvetlitev ima visoko svetlobno učinkovitost s močjo 40W. Philips 40W Upravljač Ukrepi: Ø145x170mm

### Product data

|                     |                                                           |
|---------------------|-----------------------------------------------------------|
| T° svetlobe         | 3000°K (uporabiti), 4000°K (uporabiti), 6500K (uporabiti) |
| Potrdila            | CE, ROHS                                                  |
| Prilagodljivo       | Ne                                                        |
| Stil                | Minimalističen                                            |
| Frekvenca uporabe   | Intenzivno                                                |
| Garancija           | Po zakonski garanciji: 3 leta                             |
| IP                  | IP20                                                      |
| Kelvin (K)          | 4000, 6000, 2700                                          |
| Lumeni (Lm)         | 4000, 4400                                                |
| Material            | Aluminij                                                  |
| Temperaturni razpon | -20°C ~ +40°C                                             |
| Senor               | Ne                                                        |
| Vrsta LED           | COB                                                       |
| Tonaliteta          | Topla bela, Bela hladnost, Bela nevtralna                 |
| UGR                 | Ne                                                        |
| Zunanja raba        | Ne                                                        |



Product variants

| Reference | Attributes                       |                                                                                      |
|-----------|----------------------------------|--------------------------------------------------------------------------------------|
| B7750BC   | T° svetlobe : 3000°K (uporabiti) |   |
| B7750BF   | T° svetlobe : 6500K (uporabiti)  |   |
| B7750BN   | T° svetlobe : 4000°K (uporabiti) |  |