

100lm/W

Alta eficiència
High efficiency
Haute efficacité



4W



LED circular downlight vgrajen 4W - Premer Ø77mm

4W vgrajena okrogla LED svetilka, s premerom 98 mm. Izdelan iz belega polikarbonata, ponuja učinkovito osvetlitev brez elektromagnetnega hrupa, kar ga naredi idealnega za notranje prostore. Premer rezanja: Ø77mm.

Product data

T° svetlobe	3000°K (uporabiti), 4000°K (uporabiti), 6000K (uporabiti)
Potrdila	CE, ROHS
Razred energetske učinkovitosti	A+ (2021)
CRI	80-85
Dimenzije (mm) LxLxh	98x98x25.5
Dimenzije rezanja (mm)	Ø77-82
Prilagodljivo	Ne
Učinkovitost (Lm/w)	100
Oblika	Krožno
Frekvenca uporabe	normalno
Garancija	Po zakonski garanciji: 3 leta
IP	IP20
Kelvin (K)	3000, 4000, 6000
Material difuzor	Polikarbonat
Montiranje	Vgrajen
Usmerljiv	Ne
Temperaturni razpon	-20°C ~ +40°C
Nomin Spannung (V)	230
Vrsta LED	SMD 2835
Tonaliteta	Topla bela, Bela hladnost, Bela nevtralna
Zunanja raba	Ne
Življenjska doba (h)	25000



Product variants

Reference

Attributes

B1240-B-4W-BC

T° svetlobe : 3000°K (uporabiti)



B1240-B-4W-BF

T° svetlobe : 6000K (uporabiti)



B1240-B-4W-BN

T° svetlobe : 4000°K (uporabiti)

