

100lm/W

Alta eficiencia
High efficiency
Haute efficacité



6W



LED svetilo dolge oblike vgradna 6W - Premer Ø95mm

6W vgrajen okrogel LED downlight, z zunanjim premerom 118mm in globino 25,5mm. Izdelan iz belega polikarbonata, ponuja učinkovito osvetlitev in je brez elektromagnetnega šuma, kar je idealno za notranje prostore. Premer rezanja: Ø95mm.

Product data

T° svetlobe	3000°K (uporabiti), 4000°K (uporabiti), 6000K (uporabiti)
Potrdila	CE, ROHS
Razred energetske učinkovitosti	A+ (2021)
CRI	80-85
Dimenzije (mm) LxLxh	118x118x25.5
Dimenzije rezanja (mm)	Ø95-100
Prilagodljivo	Ne
Učinkovitost (Lm/w)	100
Oblika	Krožno
Frekvenca uporabe	normalno
Garancija	Po zakonski garanciji: 3 leta
IP	IP20
Kelvin (K)	3000, 4000, 6000
Lumeni (Lm)	600
Material	Polikarbonat
Material difuzor	Polikarbonat
Montiranje	Vgrajen
Usmerljiv	Ne
Temperaturni razpon	-20°C ~ +40°C
Nomin Spannung (V)	230
Vrsta LED	SMD 2835
Tonaliteta	Topla bela, Bela hladnost, Bela nevtralna



Zunanja raba	Ne
Življenjska doba (h)	25000

Product variants

Reference	Attributes	
B1241-B-6W-BC	T° svetlobe : 3000°K (uporabiti)	 100lm/W Alta eficiencia High efficiency Haute efficacité LED 6W
B1241-B-6W-BF	T° svetlobe : 6000K (uporabiti)	 100lm/W Alta eficiencia High efficiency Haute efficacité LED 6W
B1241-B-6W-BN	T° svetlobe : 4000°K (uporabiti)	 100lm/W Alta eficiencia High efficiency Haute efficacité LED 6W