



Support Common LED Driver ICs on the Market



WS2811	SM16703	TM1814	WS2815
WS2812B	TM1804	TM1913	WS2818
WS2813	UCS1903	P9813	P943S
WS2801	LPD6803	INK1003	P9411
SK6812	LPD6806	DMA512	P9413
SK6812-RGBW	APA102	APA105	TX1812
TX1813	GS8206	GS8208	SK6822
P9414	P9412		

It can support WS2812B and WS2813. But there is no options on setting page.
Please choose WS2811 if connect it to WS2812B and WS2813.
It can't support 5050 ordinary RGB LED strips with no ICs.

WIFI RGB/RGBW pixel IC LED controller - 5-24V DC - 2048 pixels

Ref. SP108E

LED IC krmilnik je zasnovan za daljinsko upravljanje RGB/RGBW LED trakov iz mobilnega telefona. Imel ima vhodno napetost od 5 do 24V DC in lahko nadzira do 2048 pikslov. Možno je izbrati katerikoli učinek ali prizor iz 180 vnaprej nastavljenih večbarvnih vzorcev in 8 enobarvnih vzorcev. Prav tako omogoča ustvarjanje prilagojenih vzorcev iz slik. Svetlost in hitrost sta nastavljivi. Enostavno ga je nadzirati preko WiFi povezave prek aplikacije, ki jo je treba prenesti na mobilno napravo.



Product data

Potrdila	CE, ROHS
Razred energetske učinkovitosti	A+ (2021)
Konektivnost	Wifi
Garancija	3 leta
IP	IP20
Material	Plastika
Obseg zaznavanja (m)	30
Temperaturni razpon	-20°C ~ +40°C
Nomin Spannung (V)	5-24V
Tonaliteta	RGB
Zunanja raba	Ne



Product variants

Reference

Attributes

SP108E

