

LED trak 24V-DC 26W/m CRI90 enobarven IP20 Rolo 5 metrov

Product data

T° svetlobe	3000°K (uporabiti), 4000°K (uporabiti), 6500K (uporabiti)
Lepljivo	3M
Širina steze (mm)	10
Kot odprtosti (°)	120
Potrdila	CE, ROHS
Razred energetske učinkovitosti	A+ (2021)
CRI	90-95
Dimenzije (mm) LxIxh	5000x10
Prilagodljivo	Da
Razdalja reza (mm)	20
Frekvenca (Hz)	50 - 60
Frekvenca uporabe	Intenzivno
Garancija	Po zakonski garanciji: 3 leta
IP	IP20
Kelvin (K)	3000, 4000, 6000
Nosilci/metro	120
Moč (W)	130
Moč/m (W/m)	26
Nomin Spannung (V)	24V DC
Vrsta LED	SMD 2216

Tonaliteta	Topla bela, Bela hladnost, Bela nevtralna
Zunanja raba	Ne
Življenjska doba (h)	35000

Product variants

Reference	Attributes	
B1555BC	T° svetlobe : 3000°K (uporabiti)	
B1555BF	T° svetlobe : 6500K (uporabiti)	
B1555BN	T° svetlobe : 4000°K (uporabiti)	