



INPUT		LED Driver (LED 控制装置)		DALI-2	
AC-L		Model: LF-GSD040YG		Preparation for input and output	
AC-N		Input: 220-240V~50/60Hz Max.0.3A		7.5mm	
PUSH		U out: 59V= PF:>0.9C Prated:44.1W(Max)			
DA1		For 2 -Channel LED Driver			
DA2		For Australia and New Zealand, the marking label with "X"			
0.75-1.5		Output current and setting table			
		tc:90°C			
		www.lifud.com			
		Made in China			
		(中国制造)			
		CE SELV			
OUTPUT		IS Vo DC		1 2 3 4	
WW-		1050mA		OFF OFF OFF OFF	
WW+		1000mA		OFF OFF OFF ON	
CW+		900mA		OFF OFF ON OFF	
CW-		800mA		OFF OFF ON ON	
0.5-1.0		700mA		OFF ON OFF OFF	
ON		600mA		OFF ON ON OFF	
OFF		550mA		ON OFF OFF ON	

Driver LIFUD DALI-2 DT8



DALI PUSH dimmable LIFUD driver 20-42V 40W multicurrent (550-1050mA) CCT2000-7000K

Ref. LF-GSD040YG

LIFUD Driver LF-GSD040YG är en konstant ström LED-drivrutin på 40W med DALI-dimning och dimmbara funktioner. Den ingångsspänning är 220-240V och utgången är 20-42V. Dess utgångsström kan justeras från 550mA till 1050mA via DIP-brytaren, i steg om 50mA.

Product data

Certifikat	CE, ROHS
Utgångsström mA	550-1050mA
Dimensioner (mm) LxIxh	80,8x126,2x31,2mm
Ballenbar	0%-100% (0,1%)
Frekvens (Hz)	50 - 60
IP	IP20
Kelvin (K)	2000-7000K
Material	Plast
Maximal effekt (W)	40w
Temperaturområde	-20°C ~ +40°C
Utspänning (V)	20-42V
Nominell Spänning (V)	220-240V

Driver LIFUD DALI-2 DT8



Product variants

Reference

Attributes



LF-GSD040YG